


Transfusion - S93 - non-vented sets

S93 (MLL)



1. The special design of the spike enables easy penetration of container ports and offers a safe connection to the container. Non-vented version. The protection cap maintains sterility of the set.
2. Standard drip tube (20 drops/1 ml). The flexible, transparent, non-reflective material with level ring mark enables easy priming and control of drip rate. Equipped with 200 micron blood filter; filter areas Typ 93 = 11,5 cm² / Typ 88 = 23,5 cm².
3. Precision roller clamp enables exact adjustment of the desired flow rate maintaining it with minimum variation. Additionally, it is equipped with a clamp/hanging device for tubing and for protection against stick accidents after use of the set.
4. Transparent, flexible PVC tubing with plasticiser TOTM 3,0/4,1 mm (ID/OD) in the set (regular bore).
5. Male Luer-Lock adapter guarantees a safe connection to the venipuncture device. The FlowStop protection cap for Male Luer-Lock adapters with integrated hydrophobic membrane ensures internal sterility prior to use. During priming, the FlowStop protection cap remains attached to the Male Luer-Lock adapter and allows air to pass but as soon as solution reaches the membrane, the flow stops automatically.



Disclaimer:

The above is indicated only for information. This document is not a specification. The values given are subject to the usual fluctuations. Please follow the instructions for use by the medication manufacturer and the actual SPC (Summary of Product Characteristics). Common hygiene measures and working methods are to be followed at all times.

Subject to alterations without prior notice!

REF	Product description	Packaging	GTIN	Filling/Storage volume
45.4405	S93, 190 cm PVC (TOTM) tubing 3,0/4,1 mm (ID/OD), MLL adapter, FlowStop	1 100 3200	04055698025626 04055698025633 -	7 ml/1 m (40°C) 9 ml/1 m (40°C/2 bar)