




## Extension lines

### E09/2-R (2x FLL, CV, SELF-LOCK)



1. Female Luer-Lock adapter guarantees a safe connection. The protection cap maintains the sterility of the set.
2. Transparent, flexible and kink-resistant PVC tubing with plasticiser TOTM 2,5/4,1 mm (ID/OD) (regular bore).
3. Inline CODAN Check Valve
4. Slide clamp with on/off function.
5. Transparent, flexible PVC tubing with plasticiser TOTM 0,9/2,0 mm (ID/OD) (mini bore).
6. Rotating Male Luer-Lock adapter with SELF-LOCK feature for a safe and comfortable connection. FlowStop protection cap for Male Luer-Lock adapter is equipped with an integrated hydrophobic membrane, ensuring internal sterility prior to use. During priming the FlowStop protection cap remains attached to the Male Luer-Lock adapter and allows air to pass as soon as solution reaches the membrane, the flow stops automatically.



**Disclaimer:**

The above is indicated only for information. This document is not a specification. The values given are subject to the usual fluctuations. Please follow the instructions for use by the medication manufacturer and the actual SPC (Summary of Product Characteristics). Common hygiene measures and working methods are to be followed at all times.

**Subject to alterations without prior notice!**

REF	Product description	Packaging	GTIN	Filling/Storage volume
72.3183	2x FLL adapter, 2x 2,5 cm PVC (TOTM) tubing 2,5/4,1 mm (ID/OD), 2x CODAN Check Valve, 2x 150 cm PVC (TOTM) tubing 0,9/2,0 mm (ID/OD), slide clamps, SELF-LOCK, FlowStop	1 100 6300	04055698035878 04055698035885 -	3 ml (40°C) 3 ml (40°C/2 bar)



## Extension lines

### E09/2-R (2x FLL, CV, SELF-LOCK)



REF	Product description	Packaging	GTIN	Filling/Storage volume
72.3192	2x FLL adapter, 2x 2,5 cm PVC (TOTM) tubing 2,5/4,1 mm (ID/OD), 2x CODAN Check Valve, 2x 200 cm PVC (TOTM) tubing 0,9/2,0 mm (ID/OD), slide clamps, SELF-LOCK, FlowStop	1 100 6300	04055698035939 04055698035946 -	4 ml (40°C) 4 ml (40°C/2 bar)
72.3203	2x FLL adapter, 2x 2,5 cm PVC (TOTM) tubing 2,5/4,1 mm (ID/OD), 2x CODAN Check Valve, 2x 300 cm PVC (TOTM) tubing 0,9/2,0 mm (ID/OD), slide clamps, SELF-LOCK, FlowStop	1 100 6300	04055698036011 04055698036028 -	6 ml (40°C) 6 ml (40°C/2 bar)