

# evercare® Examination Gloves, Nitrile SATIN X-LONG

REF: 6520, 6521, 6522, 6523, 6524

Nitrile examination gloves and protective gloves for single use, x-long, white

### **Key Features**

- Powder-free, ambidextrous and with rolled rim for extra cuff strength.
- Excellent tactile sensitivity and enhanced wet and dry grip with micro-textured fingertips.
- Excellent fit, easy to don and remove.
- Long cuff for extended protection of wrist.
- ▶ Higher quality with AQL 1.0 of pinholes for safer use.
- Very good viral barrier properties, protects against wide variety of chemicals.
- Free of latex and proteins, good alternative to those suffering from type I allergies.



#### Recommendations for use









Basic procedures Cleaning and Pharmacy

Good	protection
o anin	at infaation

REF	DESCRIPTION	SIZE CODE	Overall Length	Pack Count dispenser/carton
6520	Examination Gloves, Nitrile SATIN X-LONG, XS, White		295 mm	100 / 1000
6521	Examination Gloves, Nitrile SATIN X-LONG, S, White		295 mm	100 / 1000
6522	Examination Gloves, Nitrile SATIN X-LONG, M, White		295 mm	100 / 1000
6523	Examination Gloves, Nitrile SATIN X-LONG, L, White		295 mm	100 / 1000
6524	Examination Gloves, Nitrile SATIN X-LONG, XL, White		295 mm	100 / 1000

Sales Unit: Transport Carton

Page 1 2024-10-01

## Regulations

The product complies with legal requirements for medical devices and personal protective equipments.



REACH regulation:	The products covered by this data sheet do not contain substances classified as carcinogenic, mutagenic or toxic for reproduction (CMR), including any of the Substances of Very High Concern (SVHC) as listed in the latest available version of the Candidate List published by European Chemicals Agency (ECHA).	
Freedom of holes:	AQL 1.0	
Force at break (N):	≥ 6.0 N (before and after challenge test)	
Biological evaluation:	EN ISO 10993-5 EN ISO 10993-10	
Compliance with legal requirements:		
Compliance with product standards: EN 455: 1 – 4		
Chemical Resistance:	Tested in accordance with EN 16523-1	
Food safety:	In accordance with EU Regulation 1935/2004 the glove is suitable for handling all foodstuffs.	
Other tests performed:	Air leak and Water leak according to EN 374-2 (Level 2) Chemicals residue Dexterity, length and pH according to EN 420 Mechanical performance according to EN 388 Microbiological quality RoHS compliance Resistance to degradation by chemicals according to EN 374-4 Viral penetration according to EN 374-5 and ASTM F1671	
Quality standards:	EN ISO 13485	
Label information and packaging compliance:	EN ISO 15223-1, EN 420, EN ISO 20417	

### Material

Product Part	Raw Material & Characteristics	
Palm	Acrylonitrile-butadiene (Nitrile), single wall thickness min. 0.07 mm	
Finger	Acrylonitrile-butadiene (Nitrile), single wall thickness min. 0.10 mm	

Page 2 2024-10-01

### Warnings & Recommendations

Warnings	The product is single use. If reused, the performance of product may deteriorate and cross contamination may occur.  The product contains dithiocarbamates – not to be used in case of hypersensitivity to these substances.		
Storage Recommendation		Recommended storage in clean, dry space in ambient temperature. Products should be protected from direct sunlight, other intensive light sources and ozone.	
Disposal Recommendation		Dispose in accordance with local regulations.	
Shelf Life		5 years	

### **Packing Information**

Package	Material	Size ( L x W x H ) mm	
Single Pack	N/A	N/A	
Dispenser Pack	TCF quality	260 x 125 x 64	
Transport Carton	TCF quality	335 x 260 x 266	
Packing Tape	PVC-free, Transparent	N/A	

#### Barcodes / UDI-DI

REF	Single Pack	Dispenser	Transport Carton
6520	N/A	06438129325539	06438129525533
6521	N/A	06438129325546	06438129525540
6522	N/A	06438129325553	06438129525557
6523	N/A	06438129325560	06438129525564
6524	N/A	06438129325577	06438129525571

Evercare Medical AB is a partner that enables better lives for patients, facilitates everyday life for healthcare employees and contributes to lower care costs. We strive to reduce the environmental impact and, together with our suppliers, to improve working conditions throughout the value chain.