



**BELMONT
MEDICAL
TECHNOLOGIES**

Saving Lives. Together.

BUDDY LITE[®] BUDDY LITE[®] AC

Safe, Compact, and Battery-Powered

PORTABLE BLOOD & FLUID WARMING



INSTANTLY
WARM PATIENTS.
ANYTIME.
ANYWHERE.



BUDDY LITE®

The buddy lite® is a portable, battery-powered, blood and fluid warmer used globally by civilian and military medical personnel to help prevent hypothermia during fluid administration.

The buddy lite® is designed to be safe, reliable, lightweight and compact. The entire system weighs less than 1.6 pounds (0.73 kg) and is small enough that it can be easily stored in medical response bags and storage compartments. The system can be set up and ready to warm in less than one minute, is capable of warming up to 4.4 liters of fluid from 20°C to 38° ± 2°C on a single charge and is approved for use in flight on battery power.

Warmed fluids are delivered through a single disposable set with standard, built-in safety features providing patient protection against vessel trauma and vascular air embolism.

WARM FLUID SAVES LIVES

Worldwide, more people under the age of 45 fall victim to trauma-related injuries than any other condition, with uncontrolled hemorrhage as the second leading cause of trauma-related death.^{1,2} A known factor associated with increased mortality in bleeding trauma victims is hypothermia (core body temperature less than 35°C). Studies have shown **up to 14% of trauma patients arrive at hospitals hypothermic**, even when transport times are short.³

Early interventions by EMS providers can significantly reduce the risk of hypothermia, slowing or even stopping Trauma's Lethal Triad of compounding issues. The addition of fluid warmers to ambulances alone has been associated with a **22% relative risk reduction in admission hypothermia**.⁴

However, heating cabinets and bag warmers are unable to overcome the impact of heat loss caused by ambient temperature conditions, resulting in line-cooling of fluid before it can reach the patient.⁵

Delivery of normothermic fluid to prevent or reduce the risk of hypothermia can be achieved using in-line fluid warmers capable of warming fluid close to the cannulation site. The buddy lite® is the only close-to-the-patient, in-line blood and fluid warmer capable of safely warming blood and fluids pre-hospital, while also **reducing the risk of inadvertent air embolism**.



BUILT-IN SAFETY

- 1 One-way valve prevents backflow from the patient
- 2 Dual heater plates gently warm fluids
- 3 Valve helps prevent air entrainment
- 4 Large venting membrane removes air from crystalloid solutions
- 5 Pressure regulating valve prevents over-pressurization of fluid line
- 6 Clamp to quickly stop fluid flow
- 7 Bed sheet clamps help secure heater by patient's side



100% ALUMINUM-FREE DISPOSABLE

Safely warms blood and fluids without the risk of exposing patients to aluminum.

AUTOMATIC AIR REMOVAL

Microporous, air-venting membrane within the fluid path designed to prevent air emboli.

CLOSE-TO-PATIENT WARMING

Warmed fluid outflow is less than 6 inches between the patient and heater to reduce line-cooldown of fluid temperature.

COMPACT & LIGHTWEIGHT

Total weight of system including heater, battery, and disposable is <725 grams (0.73 kg).

BATTERY OR AC-POWERED*

Warm up to 4.4 liters of fluid from 20°C to 38° ± 2°C on a single battery charge or switch to AC-power for continuous use.

MILITARY TESTED & APPROVED

The buddy lite™ is used extensively by United States Armed Forces as an effective method for delivering warmed fluid to injured soldiers on the field and during patient transport.

EASY TO USE

Single-button operation and pre-set outflow fluid temperature target of 38°C.

APPROVED FOR USE IN FLIGHT ON BATTERY POWER

*Optional AC-powered version available

1. Centers for Disease Control and Prevention. (Aug. 29, 2012) Web-based injury statistics query and reporting system (WISQARS). In U.S. Department of Health and Human Services, CDC, National Center for Injury Prevention and Control.
2. Kauvar DS, Lefering R & Wade CE. Impact of hemorrhage on trauma outcome: an overview of epidemiology, clinical presentations, and therapeutic considerations. J Trauma. 2006;60(6 suppl):S3-S11.
3. Lapostolle F, Sebbah JL, Couvreur J, et al. Risk factors for onset of hypothermia in trauma victims: the HypoTraum study. Crit Care. 2012;16(4):R142. Published 2012 Jul 31. doi:10.1186/cc11449
4. Waibel B. H. (2012). Hypothermia in trauma patients: predicting the big chill. Critical care (London, England), 16(5), 155. doi:10.1186/cc11473
5. Collins, N., Daly, S., Johnson, P., & Smith, G. (2015). Pre-hospital use of intravenous in-line fluid warmers to reduce morbidity and mortality for major trauma patients: A review of the current literature. Australasian Journal of Paramedicine, 12(2). doi:10.33151/ajp.12.2.139

BUDDY LITE® AC

Patient transport times to level 1 or 2 trauma centers in remote areas can exceed 60 minutes, even when transported by helicopter. The buddy lite® AC was designed to extend the warming capability of the buddy lite® when AC power is available, allowing for continuous use of the system during long transport times. The internal battery is isolated from the AC power source, conserving battery power and protecting against overcharging. The system can easily switch from AC to battery-power, eliminating any interruption in fluid resuscitation efforts.



ORDER INFORMATION

BUDDY LITE®

With 120V Charger: Part #905-00017
With 230V Charger: Part #905-00016

BUDDY LITE® AC

With 120V Charger & AC Adaptor: Part #905-00022
With 230V Charger & AC Adaptor: Part #905-00023

BUDDY LITE® W/12V VEHICLE CHARGER

Part #905-00042

BUDDY™ DISPOSABLE SET

Part #905-00010

AC/DC POWER SUPPLY

Part #111-00037

BATTERY CHARGER

120V: Part #111-00026
230V: Part #111-00027

BATTERY PACK

Part #101-00029

PRODUCT SPECIFICATIONS

WEIGHT

Heater Unit, Battery, Battery Housing: 1.6 lb. (0.73 kg)

DIMENSIONS

Battery Housing: 3.3 × 7.5 × 1.2 in. (8.4 × 19.1 × 3.1 cm)
Heater Unit: 1.5 × 5.2 × 0.9 in. (3.8 × 13.2 × 2.2 cm)
AC/DC Supply: 6.4 × 3.8 × 2.3 in. (16.2 × 9.5 × 5.7 cm)*

POWER

Battery Nominal Voltage: 14.4 VDC
Battery Recharge: ≈ 2.5 hours
AC/DC Supply: Input 100–240V AC, ± 10%, 47–63 Hz*
Single phase – Output 18 VDC 11.7A, 210W Max

DEFIBRILLATOR-PROOF TYPE CF EQUIPMENT

OPERATING PARAMETERS

Output Temperature: 38° ± 2°C
Flow Rate:

- Max 80 mL/min (Input Temperature 20°C)
- Max 50 mL/min (Input Temperature 10°C)

DISPOSABLE

Prime Volume: 7.5 mL with valves and tubing at input and output. Sterile, non-pyrogenic fluid path, single-patient use only, DEHP free, not made with natural rubber latex.

*Optional AC-powered version only

ALL DISPOSABLES ARE 100% ALUMINUM-FREE

For more information about the products we offer, contact us at sales@belmontmedtech.com.



PATIENT WARMING



PATIENT COOLING



FLUID MANAGEMENT



780 BOSTON ROAD
BILLERICA, MA 01821, USA
USA: 866.663.0212
WORLDWIDE: +1 978.663.0212
FAX: 978.663.0214
WWW.BELMONTMEDTECH.COM

The buddy lite® and buddy lite® AC have been evaluated with respect to electrical shock, fire and mechanical hazards in accordance with applicable standards.

Belmont Instrument LLC
Registered to ISO 13485
File Number: A18173

Belmont Medical Technologies™ is a trademark of Belmont Instrument, LLC
© Belmont Instrument, LLC | 701-00187 Rev. E

