

16SOFT Adult High Flow Nasal Cannula with Ribbed Connector

LATEX FREE | SINGLE PATIENT USE | DISPOSABLE

Salter-Style® 16SOFT Adult High Flow Nasal Cannula	
Reference Number	16SOFT-HF-7-25 16SOFT-HF-14-25 16SOFT-HF-25-10
Manufacturer	SunMed LLC/Salter Labs
FDA Classification	Class I Medical Device
FDA Product Code	CAT – Nasal Oxygen Cannula
Canadian MDR	Class II, Conformity Assessment Route: Medical Device License
Classifications-EU	Class IIa EC Directive 93/42/EEC Annex IX
CE Mark/ 93/42 Notified Body Number	CE 2797 / Mt Promedt Consulting GmbH
GMDN Code	35201 Nasal Cannulas
UMDNS Code	12700, Cannulae, Nasal Oxygen
Usage	Disposable, Single Patient Multiple Use
Sterile	No
Patient population	Adult
Packaging	Individually Packaged, 25/Case (for 7' & 14') Individually Packaged, 10/Case (for 25')

Device Specifications	
Description	Specification
Oxygen Supply Tubing	7' (2.1 m), 14' (4.2 m), 25' (7.6 m) Green, 3-Channel Safety Tubing
Oxygen flow rate	0 LPM to 15 LPM
Tubing End Connector	Universal Push-On Ribbed Connector
Operating temperature	5°C to 40°C
Storage temperature	-20°C to 50°C

Product Material	
Part Description	Material
Nasal face piece	Plastisol
Oxygen tubing	Polyvinylchloride
Headset tubing	Soft Durometer Polyvinylchloride
Tubing end connector	Polyvinylchloride
Bolo	Low Density Polyethylene



Intended use: Over-the-ear style nasal cannula for delivery of supplemental oxygen to nares of a spontaneously breathing patient.

Area of use: Hospitals, medical clinics, home, surgical centers, skilled nursing facilities.

Duration of use: Discard and replace nasal cannula every 14 days or sooner if the cannula becomes soiled or damaged.

Contraindications: No known.

Caution: Keep tubing straight and free of kinks. Do not sterilize.

Warning:

- If patient develops infection, skin irritation or material sensitization consult physician.
- Patient may become hypoxic if oxygen flow is interrupted.
- Position tubing to avoid strangulation or tripping hazard.
- Do not place anything on oxygen tubing that may obstruct flow.
- Use oxygen product as prescribed.
- When using oxygen, do use open flame or heat source.

Latex: Salter Labs® does not utilize latex or latex-containing material to manufacture products. To the best of our knowledge, latex does not come in contact with components or finished good during the manufacturing process.

Phthalates: The selected materials are Non-DEHP; DEHP was not intentionally added as part of the manufacturing process.

Mercury-Lead: The selected materials do not contain lead or mercury.

Biocompatible per device classification in ISO 10993. Salter Labs manufactures product from medical grade materials in compliance with Good Manufacturing Practices (GMP's) as listed in 21 C.F.R. (U.S. code of Federal Regulations).

Part Number	UOM	Tube Length	GTIN
16SOFT-HF-7	Each	7' (2.1 m)	00607411102394
16SOFT-HF-7-50	Case	7' (2.1 m)	10607411102391
16SOFT-HF-14	Each	14' (4.2 m)	00607411102400
16SOFT-HF-14-50	Case	14' (4.2 m)	10607411102407
16SOFT-HF-25	Each	25' (7.6 m)	00607411102417
16SOFT-HF-25-50	Case	25' (7.6 m)	10607411102414

TDS-10012 Rev 1

