

4560-164 Guilhufe, Penafiel - Portugal

Dry Elongation at breakTD >4,0 %

Do not sterilize by

Description:

Ref: 455-106

Technical Specifications

Brand:



-	
Final dimensions:	2.1 m x80 cm
Composition:	Cellulose,Polyethylene film.
Construction:	Drawsheets 455_7
Latex:	Free
PVC:	Free
Re use:	No
Sterilizable by:	Ethylene Oxide
Colour:	blue
Shelf life:	120 months
CFU/g	<10^2
Fluorescence	conform
Weigth/sqm	>30,0 g/m^2
Absorption EN 1644-1	Approx. 400 %
Dry Tensile strength TD	>21,0 N/5 cm
Dry Tensile strength MD	>46,5 N/5cm
Dry Elongation at breakMD	>13,3 %

Moist heat

Drawsheet



Nr and Revision Date:	5 2016/08/31	
CE Class:	I	
CE mark:	CE	
Directive:	MDD 93/42/EEC amended by 2007/47/E	
Applicable norms:	EN ISO 13485:2012; EN 1041+A1:2013; E	N ISO 11737-1:2006; EN 1041:2008;

Important Notes: Resistant,w/an impermeable side and an absorbent side

Level	Туре	Dimension	Stamp	Labels
1	120 Carton box	769x381x110mm		labeled

ENISO11737-1:2006/AC:2009; ISO 16142-1:2016; EN ISO 15 223-1:2016;

Important Notes:	Nr pcs/pack subjected to ± 3% variation		
Storage instructions	Store in a dry place at room temperature and protect from sunlight. The product has a good stability and therefore, normal conditions of medical devices storage shall apply		
Waste instructions	No special requirements. The waste must be disposed according to local legal regulations for the disposable of medical waste.		
Intended use	Protect the patient from contaminated surfaces.		

WASTE AND ENVIRONMENT REGULATIONS	Weight (gr) of packing material used in 100 pcs	513

ISSUED BY: Quality Management Department, 2018/05/16

CONFIDENTIAL: The information contained herein is confidential and belongs to Bastos Viegas, s.a. It is provided for specific purposes and in connection with established agreements. It is not permitted disclosure, reproduction, copying or distribution, in whole or in part, for other purposes or to any third parties.